




带钩数显深度尺

数据
传输

- 符合GB/T深度卡尺国家标准
- 分辨率: 0.01mm/0.0005"
- 按键: 开/关, 置零, 公/英制转换
- 自动关机, 拉动尺身开机
- CR2032电池
- 数据传输
- 不锈钢尺身



1142-150A



带数据接口

(mm)

型号	测量范围	精度	L	d	a	b	c	数据传输
1142-150A	0-150mm/0-6"	±0.03mm	230	100	5	2	14.5	数据线(型号7315-21, 7302-21, 选配)
1142-200A	0-200mm/0-8"	±0.03mm	280	100	5	2	14.5	数据线(型号7315-21, 7302-21, 选配)
1142-300A	0-300mm/0-12"	±0.04mm	380	150	5	2	14.5	数据线(型号7315-21, 7302-21, 选配)
1142-500A	0-500mm/0-20"	±0.05mm	585	150	8	3	15	数据线(型号7315-22, 7302-22, 选配)
1142-5001A	0-500mm/0-20"	±0.05mm	585	200	8	3	15	数据线(型号7315-22, 7302-22, 选配)
1142-1000A	0-1000mm/0-40"	±0.07mm	1188	150	10	4	18	数据线(型号7315-22, 7302-22, 选配)
1142-10001A	0-1000mm/0-40"	±0.07mm	1188	200	10	4	18	数据线(型号7315-22, 7302-22, 选配)
1142-10002A	0-1000mm/0-40"	±0.07mm	1188	250	10	4	18	数据线(型号7315-22, 7302-22, 选配)

内置无线(需选配接收器, 型号7315-2/3/6/7/8/9)

(mm)

型号	测量范围	精度	L	d	a	b	c
1142-150AWL	0-150mm/0-6"	±0.03mm	230	100	5	2	14.5
1142-200AWL	0-200mm/0-8"	±0.03mm	280	100	5	2	14.5
1142-300AWL	0-300mm/0-12"	±0.04mm	380	150	5	2	14.5
1142-500AWL	0-500mm/0-20"	±0.05mm	585	150	8	3	15
1142-5001AWL	0-500mm/0-20"	±0.05mm	585	200	8	3	15
1142-1000AWL	0-1000mm/0-40"	±0.07mm	1188	150	10	4	18
1142-10001AWL	0-1000mm/0-40"	±0.07mm	1188	200	10	4	18
1142-10002AWL	0-1000mm/0-40"	±0.07mm	1188	250	10	4	18

