

- 符合GB/T普通螺纹量规国家标准
- 由含钨工具钢制成, 油淬火, 超低温处理
- 产品的耐磨性好, 寿命长, 尺寸稳定, 光洁度高
- 硬度HRC60-62
- 带生产厂检验证书



4631-12



4631-12N

\* 型号说明举例:

公称直径	螺距	等级6h
		GO(通)
M1	0.25	-1H

型号为4631-1H

规格(mm)		型号(4631)*					
		等级6g		等级6e		等级6h	
公称直径	螺距	GO(通)	NOGO(止)	GO(通)	NOGO(止)	GO(通)	NOGO(止)
M1	0.25	—	—	—	—	-1H	-1HN
M1.1	0.25	—	—	—	—	-1D1H	-1D1HN
M1.2	0.25	—	—	—	—	-1D2H	-1D2HN
M1.4	0.3	—	—	—	—	-1D4H	-1D4HN
M1.6	0.35	-1D6	-1D6N	-1D6E	-1D6EN	-1D6H	-1D6HN
M1.7	0.35	-1D7	-1D7N	—	—	—	—
M1.8	0.35	-1D8	-1D8N	—	—	-1D8H	-1D8HN
M2	0.4	-2	-2N	-2E	-2EN	-2H	-2HN
M2.2	0.45	-2D2	-2D2N	-2D2E	-2D2EN	-2D2H	-2D2HN
M2.3	0.4	-2D3	-2D3N	—	—	—	—
M2.5	0.45	-2D5	-2D5N	-2D5E	-2D5EN	-2D5H	-2D5HN
M2.6	0.45	-2D6	-2D6N	—	—	—	—
M3	0.5	-3	-3N	-3E	-3EN	-3H	-3HN
M3.5	0.6	-3D5	-3D5N	-3D5E	-3D5EN	-3D5H	-3D5HN
M4	0.7	-4	-4N	-4E	-4EN	-4H	-4HN
M4.5	0.75	-4D5	-4D5N	—	—	—	—
M5	0.8	-5	-5N	-5E	-5EN	-5H	-5HN
M6	1	-6	-6N	-6E	-6EN	-6H	-6HN
M7	1	-7	-7N	-7E	-7EN	-7H	-7HN
M8	1.25	-8	-8N	-8E	-8EN	-8H	-8HN
M9	1.25	-9	-9N	-9E	-9EN	-9H	-9HN
M10	1.5	-10	-10N	-10E	-10EN	-10H	-10HN

规格(mm)		型号(4631)*					
		等级6g		等级6e		等级6h	
公称直径	螺距	GO(通)	NOGO(止)	GO(通)	NOGO(止)	GO(通)	NOGO(止)
M11	1.5	-11	-11N	-11E	-11EN	-11H	-11HN
M12	1.75	-12	-12N	-12E	-12EN	-12H	-12HN
M14	2	-14	-14N	-14E	-14EN	-14H	-14HN
M16	2	-16	-16N	-16E	-16EN	-16H	-16HN
M18	2.5	-18	-18N	-18E	-18EN	-18H	-18HN
M20	2.5	-20	-20N	-20E	-20EN	-20H	-20HN
M22	2.5	-22	-22N	-22E	-22EN	-22H	-22HN
M24	3	-24	-24N	-24E	-24EN	-24H	-24HN
M27	3	-27	-27N	-27E	-27EN	-27H	-27HN
M30	3.5	-30	-30N	-30E	-30EN	-30H	-30HN
M33	3.5	-33	-33N	-33E	-33EN	-33H	-33HN
M36	4	-36	-36N	-36E	-36EN	-36H	-36HN
M39	4	-39	-39N	-39E	-39EN	-39H	-39HN
M42	4.5	-42	-42N	—	—	-42H	-42HN
M45	4.5	-45	-45N	—	—	-45H	-45HN
M48	5	-48	-48N	—	—	-48H	-48HN
M52	5	-52	-52N	—	—	-52H	-52HN
M56	5.5	-56	-56N	—	—	—	—
M60	5.5	-60	-60N	—	—	—	—
M64	6	-64	-64N	—	—	—	—
M68	6	-68	-68N	—	—	—	—