



惠氏圆柱管螺纹环规(G系列)



4635-1A14



4635-1A14N

- 符合ISO228标准
- 由含钨工具钢制成, 油淬火, 超低温处理
- 产品的耐磨性好, 寿命长, 尺寸稳定, 光洁度高
- 硬度HRC60-62
- 带生产厂检验证书(规格G 4-11及以上不带)

规格	型号			
	等级A		等级B	
	GO(通)	NOGO(止)	GO(通)	NOGO(止)
G 1/16-28	4635-1D28	4635-1D28N	—	—
G 1/8-28	4635-1C28	4635-1C28N	4635-1C28B	4635-1C28BN
G 1/4-19	4635-1B19	4635-1B19N	4635-1B19B	4635-1B19BN
G 3/8-19	4635-3C19	4635-3C19N	4635-3C19B	4635-3C19BN
G 1/2-14	4635-1A14	4635-1A14N	4635-1A14B	4635-1A14BN
G 5/8-14	4635-5C14	4635-5C14N	—	—
G 3/4-14	4635-3B14	4635-3B14N	4635-3B14B	4635-3B14BN
G 7/8-14	4635-7C14	4635-7C14N	—	—
G 1-11	4635-111	4635-111N	4635-111B	4635-111BN
G 1 1/8-11	4635-1F11	4635-1F11N	—	—
G 1 1/4-11	4635-1G11	4635-1G11N	—	—
G 1 1/2-11	4635-1H11	4635-1H11N	4635-1H11B	4635-1H11BN

规格	型号	
	等级A	
	GO(通)	NOGO(止)
G 1 3/4-11	4635-3G11	4635-3G11N
G 2-11	4635-211	4635-211N
G 2 1/4-11	4635-1K11	4635-1K11N
G 2 1/2-11	4635-1J11	4635-1J11N
G 2 3/4-11	4635-3K11	4635-3K11N
G 3-11	4635-311	4635-311N
G 3 1/2-11	4635-1N11	4635-1N11N
G 4-11	4635-411	4635-411N
G 4 1/2-11	4635-1S11	4635-1S11N
G 5-11	4635-511	4635-511N
G 5 1/2-11	4635-1W11	4635-1W11N
G 6-11	4635-611	4635-611N