

- 符合BS 919-2标准
- 由工具钢制成, 退火后反复调质, 尺寸稳定
- 产品的耐磨性好, 寿命长, 光洁度高
- 硬度≥HRC62
- 带生产厂检验证书



4694-1B26



4694-1B26N

| 规格              | 型号         |             |
|-----------------|------------|-------------|
|                 | GO(通)      | NOGO(止)     |
| BSF3/16-32-med  | 4694-3B32  | 4694-3B32N  |
| BSF7/32-28-med  | 4694-7W28  | 4694-7W28N  |
| BSF1/4-26-med   | 4694-1B26  | 4694-1B26N  |
| BSF9/32-26-med  | 4694-9W26  | 4694-9W26N  |
| BSF5/16-22-med  | 4694-5D22  | 4694-5D22N  |
| BSF3/8-20-med   | 4694-3C20  | 4694-3C20N  |
| BSF7/16-18-med  | 4694-7D18  | 4694-7D18N  |
| BSF1/2-16-med   | 4694-1A16  | 4694-1A16N  |
| BSF9/16-16-med  | 4694-9D16  | 4694-9D16N  |
| BSF5/8-14-med   | 4694-5C14  | 4694-5C14N  |
| BSF11/16-14-med | 4694-11D14 | 4694-11D14N |
| BSF3/4-12-med   | 4694-3B12  | 4694-3B12N  |
| BSF7/8-11-med   | 4694-7C11  | 4694-7C11N  |
| BSF1-10-med     | 4694-2A10  | 4694-2A10N  |