


螺距规

INSIZE PLUS

注意: 精度不符合JJG螺纹样板国家计量检定规程

- 符合企业标准, 精度不符合JJG螺纹样板国家计量检定规程
- 材质: 碳素钢
- 精度: 公制: $\pm 0.03\text{mm}$ (螺距0.25~1.3mm)
 $\pm 0.05\text{mm}$ (螺距1.4~7.0mm)
 $\pm 0.07\text{mm}$ (螺距7.5~11.5mm)
 美制统一标准, 英制惠氏标准: $\pm 0.03\text{mm}$ (80~40TPI)
 $\pm 0.05\text{mm}$ (38~10TPI)
 $\pm 0.07\text{mm}$ (9~3-1/2TPI)



公制螺纹60°

型号	测量范围	包含的尺片螺距(mm)	尺片数量
4825-128	0.25-2.5mm	0.25, 0.3, 0.35, 0.4, 0.45, 0.5, 0.55, 0.6, 0.65, 0.7, 0.75, 0.8, 0.85, 0.9, 1.0, 1.1, 1.2, 1.25, 1.3, 1.4, 1.5, 1.6, 1.7, 1.75, 1.8, 1.9, 2.0, 2.5	28
4825-123	0.2-6.0mm	0.2, 0.25, 0.35, 0.4, 0.45, 0.5, 0.6, 0.7, 0.75, 0.8, 1.0, 1.25, 1.5, 1.75, 2.0, 2.5, 3.0, 3.5, 4.0, 4.5, 5.0, 5.5, 6.0	23
4825-117	0.5-7.0mm	0.5, 0.75, 1.0, 1.25, 1.5, 1.75, 2.0, 2.5, 3.0, 3.5, 4.0, 4.5, 5.0, 5.5, 6.0, 6.5, 7.0	17
4825-122	1.0-11.5mm	1.0, 1.5, 2.0, 2.5, 3.0, 3.5, 4.0, 4.5, 5.0, 5.5, 6.0, 6.5, 7.0, 7.5, 8.0, 8.5, 9.0, 9.5, 10.0, 10.5, 11.0, 11.5	22

英制惠氏螺纹55°

型号	测量范围	包含的每英寸牙数	尺片数量
4825-230	3 1/2-60TPI	3 1/2, 4, 4 1/2, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 16, 18, 19, 20, 22, 24, 25, 26, 28, 30, 32, 36, 40, 44, 48, 50, 60TPI	30
4825-226	4-60TPI	4, 4 1/2, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 16, 18, 19, 20, 22, 24, 25, 26, 28, 30, 32, 40, 48, 60TPI	26

美制统一螺纹60°

型号	测量范围	包含的每英寸牙数	尺片数量
4825-334	3-80TPI	3, 3 1/2, 4, 4 1/2, 5, 5 1/2, 6, 7, 8, 9, 10, 11, 12, 13, 14, 16, 18, 20, 22, 24, 26, 28, 30, 32, 36, 40, 44, 48, 50, 56, 60, 64, 72, 80TPI	34
4825-324	4-30TPI	4, 4 1/2, 5, 5 1/2, 6, 7, 8, 9, 10, 11, 11 1/2, 12, 13, 14, 15, 16, 18, 20, 22, 24, 26, 27, 28, 30TPI	24
4825-330	4-42TPI	4, 4 1/2, 5, 5 1/2, 6, 7, 8, 9, 10, 11, 11 1/2, 12, 13, 14, 15, 16, 18, 20, 22, 24, 26, 27, 28, 30, 32, 34, 36, 38, 40, 42TPI	30
4825-328	4-80TPI	4, 4 1/2, 5, 6, 7, 8, 9, 10, 11, 11 1/2, 12, 13, 14, 16, 18, 20, 24, 27, 28, 32, 36, 40, 44, 48, 56, 64, 72, 80TPI	28
4825-351	4-84TPI	4, 4 1/2, 5, 5 1/2, 6, 7, 8, 9, 10, 11, 11 1/2, 12, 13, 14, 15, 16, 18, 20, 22, 24, 26, 27, 28, 30, 32, 34, 36, 38, 40, 42, 44, 46, 48, 50, 52, 54, 56, 58, 60, 62, 64, 66, 68, 70, 72, 74, 76, 78, 80, 82, 84TPI	51
4825-330A	6-60TPI	6, 7, 8, 9, 10, 11, 11 1/2, 12, 13, 14, 15, 16, 18, 20, 22, 24, 26, 27, 28, 30, 32, 34, 36, 38, 40, 42, 48, 50, 56, 60TPI	30
4825-322	9-40TPI	9, 10, 11, 11 1/2, 12, 13, 14, 15, 16, 18, 20, 22, 24, 26, 27, 28, 30, 32, 34, 36, 38, 40TPI	22

公制螺纹60°和美制统一螺纹60°组合

型号	测量范围	包含的螺距或每英寸牙数	尺片数量
4825-451	0.4-6.0mm	0.4, 0.45, 0.5, 0.6, 0.7, 0.75, 0.8, 0.9, 1.0, 1.25, 1.5, 1.75, 2.0, 2.5, 3.0, 3.5, 4.0, 4.5, 5.0, 5.5, 6.0mm	51
	4-42TPI	4, 4 1/2, 5, 5 1/2, 6, 7, 8, 9, 10, 11, 11 1/2, 12, 13, 14, 15, 16, 18, 20, 22, 24, 26, 27, 28, 30, 32, 34, 36, 38, 40, 42TPI	

公制螺纹60°和英制惠氏螺纹55°组合

型号	测量范围	包含的螺距或每英寸牙数	尺片数量
4825-552	0.25-6.0mm	0.25, 0.3, 0.35, 0.4, 0.45, 0.5, 0.6, 0.7, 0.75, 0.8, 0.9, 1.0, 1.25, 1.5, 1.75, 2.0, 2.5, 3.0, 3.5, 4.0, 4.5, 5.0, 5.5, 6.0mm	52
	4-62TPI	4, 4 1/2, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 16, 18, 19, 20, 22, 24, 25, 26, 28, 30, 32, 36, 40, 48, 60, 62TPI	