

陶瓷光滑极限塞规




定制塞规

可定制其它等级, 如H8, H9, G7
可定制直径, 如19.003mm
可定制长度, 如70mm



6332-17C

- 符合JJG光滑极限量规国家计量检定规程
- 包含通规和止规
- 氧化锆陶瓷材料制成, 耐磨性好, 耐腐蚀性好, 尺寸稳定性好



H7尺寸公差

(mm)

直径(mm)	Ød1 通规尺寸公差(mm)	Ød2 止规尺寸公差(mm)	L1	L2	L
≥0.5, ≤3	+0.0010/+0.0022	+0.0088/ +0.010	20	15	95
>3, ≤6	+0.0013/+0.0027	+0.0106/+0.012	20	15	95
>6, ≤10	+0.0015/+0.0033	+0.0132/+0.015	20	15	95
>10, ≤15	+0.0018/+0.0038	+0.0160/+0.018	20	15	95
>15, ≤18	+0.0018/+0.0038	+0.0160/+0.018	20	15	115
>18, ≤30	+0.0023/+0.0046	+0.0186/+0.021	20	15	115
>30, ≤50	+0.0023/+0.0055	+0.0220/+0.025	20	15	115

H7

型号	直径(mm)
6332-1C*	1
6332-2C*	2
6332-3C*	3
6332-4C*	4
6332-5C*	5
6332-6C*	6
6332-7C*	7
6332-8C*	8
6332-9C*	9
6332-10C*	10
6332-11C*	11
6332-12C*	12
6332-13C*	13

型号	直径(mm)
6332-14C*	14
6332-15C*	15
6332-16C*	16
6332-17C*	17
6332-18C*	18
6332-19C*	19
6332-20C*	20
6332-21C*	21
6332-22C*	22
6332-23C*	23
6332-24C*	24
6332-25C*	25
6332-26C*	26

型号	直径(mm)
6332-27C*	27
6332-28C*	28
6332-29C*	29
6332-30C*	30
6332-31C*	31
6332-32C*	32
6332-33C*	33
6332-34C*	34
6332-35C*	35
6332-36C*	36
6332-37C*	37
6332-38C*	38
6332-39C*	39

型号	直径(mm)
6332-40C*	40
6332-41C*	41
6332-42C*	42
6332-43C*	43
6332-44C*	44
6332-45C*	45
6332-46C*	46
6332-47C*	47
6332-48C*	48
6332-49C*	49
6332-50C*	50

*带生产厂检验证书