

陶瓷光滑极限塞规(单头)




定制塞规
 可定制其它等级, 如H8, H9, G7
 可定制直径, 如19.003mm
 可定制长度, 如70mm



6333-10C

- 符合JJG光滑极限量规国家计量检定规程
- 包含通规和止规
- 氧化锆陶瓷材料制成, 耐磨性好, 耐腐蚀性好, 尺寸稳定性好



H7尺寸公差 (mm)

直径(mm)	Ød1 通规尺寸公差(mm)	Ød2 止规尺寸公差(mm)	L1	L2	L
≥0.5, ≤3	+0.0010/+0.0022	+0.0088/+0.010	20	15	95
>3, ≤6	+0.0013/+0.0027	+0.0106/+0.012	20	15	95
>6, ≤10	+0.0015/+0.0033	+0.0132/+0.015	20	15	95
>10, ≤15	+0.0018/+0.0038	+0.0160/+0.018	20	15	95
>15, ≤18	+0.0018/+0.0038	+0.0160/+0.018	20	15	115
>18, ≤30	+0.0023/+0.0046	+0.0186/+0.021	20	15	115
>30, ≤40	+0.0023/+0.0055	+0.0220/+0.025	20	15	115

H7

型号	直径(mm)
6333-1C*	1
6333-2C*	2
6333-3C*	3
6333-4C*	4
6333-5C*	5
6333-6C*	6
6333-7C*	7
6333-8C*	8
6333-9C*	9
6333-10C*	10
6333-11C*	11

型号	直径(mm)
6333-12C*	12
6333-13C*	13
6333-14C*	14
6333-15C*	15
6333-16C*	16
6333-17C*	17
6333-18C*	18
6333-19C*	19
6333-20C*	20
6333-21C*	21
6333-22C*	22

型号	直径(mm)
6333-23C*	23
6333-24C*	24
6333-25C*	25
6333-26C*	26
6333-27C*	27
6333-28C*	28
6333-29C*	29
6333-30C*	30
6333-31C*	31
6333-32C*	32
6333-33C*	33

型号	直径(mm)
6333-34C*	34
6333-35C*	35
6333-36C*	36
6333-37C*	37
6333-38C*	38
6333-39C*	39
6333-40C*	40

*带生产厂检验证书