

# 可换头机械扭矩扳手(数显设置)



注意: 显示预设的扭矩值  
(不显示实际扭矩)

注意: 仅限于  
顺时针方向使用

- 符合JJG扭矩扳子国家计量检定规程
- 单位: N.m, in.lb, ft.lb, kg.cm
- 使用方法与机械扭矩扳手一致, 数显设置扭矩值



## 技术参数

型号	IST-25WM60	IST-25WM100	IST-25WM140	IST-25WM200	IST-25WM300
扭矩范围(顺时针)	12~60N.m	20~100N.m	28~140N.m	40~200N.m	60~300N.m
精度	±3%	±3%	±3%	±3%	±3%
分度值	0.1N.m	0.1N.m	0.1N.m	0.1N.m	0.1N.m
安装槽尺寸(A×B)	12×9mm	12×9mm	18×14mm	18×14mm	18×14mm
长度	408mm	431mm	492mm	510mm	568mm
重量	1.3kg	1.4kg	1.45kg	1.5kg	1.7kg



## 棘轮头部(选配)

型号	棘轮方头尺寸	适用的扳手
IST-11WM-R1	1/4"	IST-25WM60, IST-25WM100
IST-11WM-R2	3/8"	IST-25WM60, IST-25WM100
IST-11WM-R3	1/2"	IST-25WM140, IST-25WM200 IST-25WM300
IST-11WM-R4 *	3/4"	IST-25WM140, IST-25WM200 IST-25WM300



## 钩形头部(选配)

钩形头部	根据客户要求定制
------	----------



开口扳手头部(选配)

型号	开口尺寸	适用的扳手	
IST-11WM-K6	6mm	IST-25WM60 IST-25WM100	
IST-11WM-K7	7mm		
IST-11WM-K8	8mm		
IST-11WM-K9	9mm		
IST-11WM-K10	10mm		
IST-11WM-K11	11mm		
IST-11WM-K12	12mm		
IST-11WM-K13	13mm		
IST-11WM-K14	14mm		
IST-11WM-K15	15mm		
IST-11WM-K16	16mm		
IST-11WM-K17	17mm		
IST-11WM-K18*	18mm		
IST-11WM-K19*	19mm		
IST-11WM-K13A	13mm		IST-25WM140 IST-25WM200 IST-25WM300
IST-11WM-K14A	14mm		
IST-11WM-K15A	15mm		
IST-11WM-K16A	16mm		
IST-11WM-K17A	17mm		
IST-11WM-K18A	18mm		
IST-11WM-K19A	19mm		
IST-11WM-K20A	20mm		
IST-11WM-K21A	21mm		
IST-11WM-K22A	22mm		
IST-11WM-K23A	23mm		
IST-11WM-K24A	24mm		
IST-11WM-K27A*	27mm		
IST-11WM-K30A*	30mm		
IST-11WM-K32A*	32mm		

\*更换头部后需要修正扭矩值



梅花扳手头部(选配)

型号	开口尺寸	适用的扳手
IST-11WM-M8	8mm	IST-25WM60 IST-25WM100
IST-11WM-M10	10mm	
IST-11WM-M13	13mm	
IST-11WM-M14	14mm	
IST-11WM-M15	15mm	
IST-11WM-M17	17mm	
IST-11WM-M19	19mm	
IST-11WM-M13A	13mm	IST-25WM140 IST-25WM200 IST-25WM300
IST-11WM-M14A	14mm	
IST-11WM-M15A	15mm	
IST-11WM-M17A	17mm	
IST-11WM-M19A	19mm	
IST-11WM-M22A	22mm	
IST-11WM-M24A	24mm	
IST-11WM-M27A*	27mm	
IST-11WM-M30A*	30mm	
IST-11WM-M32A*	32mm	